

Permenant Oil Booms

POB 1 / POB 2



Tritonbuoys permanent oil booms are constructed from high-grade materials to ensure exceptional durability and longevity. They are produced in fixed-length sections, facilitating easy deployment and adjustment to meet specific needs. This design ensures reliable performance and adaptability in various conditions.

Product Code: POB 1 / POB 2

Tritonbuoys permanent oil booms are expertly designed for containing the spread of oil and other surface contaminants in medium to high-current environments, such as around intake towers. Their robust construction ensures effective containment and control in more challenging water conditions.

Features:

- High grade materials.
- Optional navigation lights available.
- Easy deployment.
- Durable.



	POB1	POB2
General Characteristics		
Floatation Section	Rotomolded Polyethylene Floats	
Skirt	6-8mm Reinforced Rubber Belt	12-14 mm Reinforced Rubber Belt
Skirt Ballast	HDG/SS Plates	
Connectors	HDPE, SS316, HDG	
Draft	0.5 - 2.5 m	0.5 - 3 m
Boom Section Length	20 m	20 m
Certifications		
Quality Assurance	ISO9001:2015	
Options Available		
Demarcation Lighting, Marker Buoys, Mooring Systems, Signage Buoys		
Customisation to client requirements		

* Specifications subject to change or variation without notice
** Warranty subject to terms & conditions